FLEXO TIGHTWEAVE

GENERAL PURPOSE
Technical Data Sheet

FLEXO® TIGHT WEAVE

TIGHT WEAVE FOR COMPLETE COVERAGE · RESISTS GASOLINE, ENGINE CHEMICALS, AND CLEANING SOLVENTS · CUT & ABRASION RESISTANCE

The FLEXO® Tight Weave original braided from 10 mil polyethylene terephthalate (PET) monofilament yarns. The material has a wide operating temperature range, is resistant to chemical degradation, UV radiation, and abrasion. Tight Weave is designed for use in applications where optimum coverage and abrasion resistance is required. The tight braid construction increases the coverage, wear factor and improves harness security. Used in electronics, automotive, marine and industrial wire harnessing applications where cost efficiency and durability are critical.

SIZING CHART

Nominal Size	Part #	Min Expansion	Max Expansion	*Put-Ups		Available Colors	Lbs/ 100'
				M	L		
1/8"	PTT0.13	1/16"	1/4"	225'	1,000'	5	0.29
1/4"	PTT0.25	11/64"	5/16"	200'	1,000'	5	0.36
5/16"	PTT0.31	1/4"	3/8"	200'	1,000'	5	0.58
1/2"	PTT0.50	11/32"	5/8"	100'	500'	5	0.84
3/4"	PTT0.75	1/2"	13/16"	100'	250'	5	1.10
1"	PTT1.00	5/8"	1 1/8"	100'	250'	5	1.23
1 1/4"	PTT1.25	1"	1 11/16"	50'	250'	5	1.30
1 1/2"	PTT1.50	1 1/8"	2"	40'	200'	5	1.95
1 3/4"	PTT1.75	1 1/2"	2 5/8"	30'	200'	5	2.60
2"	PTT2.00	1 3/4	3 1/8"	50'	200'	5	3.43
2 1/2 "	PTT2.50	2"	3 1/2"	50'	100'	5	3.60

*Put-Ups: ***"M"*** = Shop Spool and ***"L"*** = Bulk Spool



FEATURES

Material	**Polyethylene Terephthalate**
Grade	**PTT**
Monofilament Diameter	**.010"**
Drawing Number	**TF001PET-WD**
Cutting	**Hot Knife**

COLORS



Black & Neon Blue (BNB), Black & Neon Red (BNR), Black & Neon Orange (BNO), Black & Neon Yellow (BNY), & Black (BK)

*** For more custom colors please call your sales representative*

CERTIFICATIONS

ABYC · Prop 65 CLEAN · UL · Recycle · CSA · RoHS Compliant · FAR-25

TECHFLEX
Braided Sleeving Products